

GROB 4V-24 Series Metal Cutting Band Saw



- •Cold rolled gears and splines for superior strength.
- •Heavy duty construction.
- •4 speed gear box.
- •Air blower (shop air required).
- •Work light.
- •Speed Range of 40 5000 FPM
- Speed Indicator
- •3 HP 208/230/460 Volt 3 Phase, 60 Cycle motor
- Optional single phase or 575 Volt
- •Frequency Drive with Dynamic Braking or Standard On/Off Button
- •Ball bearing mounted balanced aluminum pulleys.
- •Single door, dust proof electrical enclosure with disconnect switch.
- Door safety switches.
- •One (1) pair 3/8" 1/2" aluminum bronze saw guides and holders included
- •24" throat.
- •Dimensions & weight for shipping 88" x 54" x 48" 1790 LBS

4V-24 with 12" work height			15,050.00	
ABOVE with 20" work height, add			2,950.00	
Select Voltage	208V			
	230V			
	480V			
Select One	Standard On/Off buttons			
	Variable Drive			

OPTIONAL EQUIPMENT

AIR HYDRAULIC FEED (REQUIRES AIR SUPPLY)	\$ 3,000.00	
RIP FENCE	\$ 750.00	
MITER GAGE (18248)	\$ 600.00	
CIRCULAR CUTTING ATTACHMENT	\$ 1,450.00	
RWA WELDER	\$ 3,550.00	
RWA WELDER WITH GRINDER	\$ 3,950.00	
MIST COOLANT (REQUIRES AIR SUPPLY) EWH SAWS USE 4V-36 UNIT	\$ 975.00	

